

SUNBRELLA PLUS XL

Technical sheet



| CHARACTERISTICS | VALUES | | UNITS | STANDARDS |
|-----------------|--------|------|-------|-----------|
| | WARP | WEFT | | |

GENERAL CHARACTERISTICS

| | | | | |
|------------------|---|--|------------------|------------|
| Composition | 100% Sunbrella acrylic | | | |
| Backing / Finish | Water repellent treatment - easy to clean. Polyurethane coating one side water and UV - resistant | | | |
| Weave | Canvas | | | ISO 7211-1 |
| Weight | 320 | | g/m ² | ISO 3801 |
| Width | 200 | | cm | EN 1773 |
| Roll length | 35 | | m | |

FABRIC RESISTANCE

| | | | | |
|---------------------------|------|-----|---------------------|-------------|
| Tensile strength | 140 | 130 | daN/5cm | ISO 13934-1 |
| Elongation at break | 30 | 15 | % | ISO 13934-1 |
| Tear strength | 3.3 | 2.5 | daN | ISO 13937-1 |
| Schmerber | 1000 | | mm | ISO 811 |
| Spray test | 4 | | Class / 5 | ISO 4920 |
| Oil-resistance properties | 5 | | Class / 8 | ISO 14419 |
| Air permeability | 2.5 | | l/m ² /s | ISO 9237 |

COLOUR-FASTNESS

| | | | | |
|--------------------------------------|-----|--|-----------|-------------|
| Colour fastness UV - outdoor - 1000h | 4-5 | | Class / 5 | ISO 105 B04 |
| Colour fastness UV - indoor | 7-8 | | Class / 8 | ISO 105 B02 |
| Colour fastness under dry friction | 5 | | Class / 5 | ISO 105X12 |
| Colour fastness under wet friction | 5 | | Class / 5 | ISO 105X12 |

USES

| | | | | |
|------------------|--|-------|--|--|
| Guarantee | 5 | years | | |
| Recommended Uses | Sprayhood, Rear enclosure, Bimini top, Cockpit enclosure, Windscreen cover, Dodger, Console cover, Lazybag | | | |

This product's values may vary with a tolerance of ± 5%

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com/en/UK

