

SWK6 (SUNWORKER)

Tekniskt blad



EGENSKAPER	VÄRDEN		ENHETER	STANDARDER
	VARP	VÅFT		

ALLMÄNNA EGENSKAPER

Komposition	Höghållfast polyester/PVC 50/50			
Ytbehandling	Dubbsidig PVC-beläggning – system Lowick			
Väv	Rachel Trameur – överlägsen rivstyrka			
Vikt	300		g/m ²	ISO 3801
Tjocklek	0.42		mm	ISO 5084
Öppningsfaktor	6		%	
Vinkelavvikelse	<2			
Bredder	150 300		cm	EN 1773
Rullängd	60 30		ml	

TYGMOTSTÅND

Rivstyrka	220	150	daN/5cm	ISO 13934-1
Brothållfasthet	32	30	%	ISO 13934-1
Rivhållfasthet	50	30	daN	DIN 53.363
Styvhet	1100	450	mN	ISO 2493
Töjning under belastning	1.5	4.2	%	MO LAB 025
Hållbarhet	4		Class / 4	EN 13561
Resistens mot eld / Euroklass	B s2 d0			EN 13501-1
Resistens mot eld / FR	M1			NF P 92 503
Resistens mot eld / DE	B1			DIN 4102
Resistens mot eld / IT	C1			UNI 9176
Resistens mot eld / ES	Clase 1			UNE-EN 13773
Ljudabsorption	0.15			ISO 354

FÄRGBESTÄNDIGHET

Färgbästendighet UV utomhus - 1000h	4.5 or 4		Class / 5	ISO 105 B04
Färgbästendighet UV inomhus	7		Class / 8	ISO 105 B02
färgbästendighet	4 or 3		Class / 4	EN 13561

TILLÄMPNINGAR

Användningstemperatur	-30 >> +70		
Garanti	5	år	
Rekommenderad användning	Vertical blind, veranda, shade sail, velum, pergola, acoustic panel, stretched wall, stretched ceiling		

ANMÄRKNINGAR

Anmärknningar	<p>These technical specifications are average values with a tolerance of +/-5%. All the specifications featured in this datasheet are for information only and do not constitute a guarantee. Their sole purpose is to provide a general description of the products. They may not be construed as a contractual commitment on our part. It is the customer's responsibility to check the validity of this information and the compliance of the merchandise received prior to installation, carrying out preliminary tests if necessary. It is also his/her responsibility to ensure that the selected product is suitable for its intended use. The customer is responsible for using the product under normal foreseeable conditions and in accordance with all safety and environmental regulations currently in force in the place of use as well as the professional standards of his/her sector. Dickson Constant reserves the right to withdraw from the market any of the products that feature in this data sheet and/or to amend the related specifications.</p>
---------------	---



Värdena för denna produkt kan variera \pm 5%

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com/en/UK