

VELUM XL

Technical sheet



CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

GENERAL CHARACTERISTICS

Composition	100% Sunbrella Acrylic			
Backing / Finish	Water-repellent & Stain-proof			
Weave	Velum			ISO 7211-1
Weight	160		g/m ²	ISO 3801
Thickness	0.5		mm	ISO 5084
Width	300		cm	EN 1773
Roll length	40		ml	

FABRIC RESISTANCE

Tensile strength	100	70	daN/5cm	ISO 13934-1
Elongation at break	25	30	%	ISO 13934-1
Oil-resistance properties	3		Class / 8	ISO 14419
Stability on 30 deg. C washing	±2	±0.5	%	ISO 5077
Steam stability	1	1	%	

COLOUR-FASTNESS

Colour fastness UV - outdoor - 1000h	4/5		Class / 5	ISO 105 B04
Colour fastness UV - indoor	8		Class / 8	ISO 105 B02
Colour fastness under dry friction	5		Class / 5	ISO 105X12
Colour fastness under wet friction	5		Class / 5	ISO 105X12
Colour fastness 40°C washing	5		Class / 5	ISO 105 C06

USES

Guarantee	5	years	
Recommended Uses	curtains, pergolas		

CARE



This product's values may vary with a tolerance of ± 5%

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com/en/UK

