

SUNBRELLA REEF

Technical sheet



CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

GENERAL CHARACTERISTICS

Composition	100% Sunbrella acrylic			
Backing / Finish	Water-repellent & Stain-proof			
Weave	Jacquard			ISO 7211-1
Weight	393		g/m ²	ISO 3801
Width	140		cm	EN 1773
Roll length	45		m	



FABRIC RESISTANCE

Tensile strength	108	201	daN/5cm	ISO 13934-1
Elongation at break	21	30	%	ISO 13934-1
Schmerber	94		mm	ISO 811
Spray test	5		Class / 5	ISO 4920
Oil-resistance properties	5		Class / 8	ISO 14419
Seam slippage (180 N)	< 8	< 4	mm	ISO 13936-2
Stitching strength	478	493	daN	ISO 13935-2
Stability on 30 deg. C washing	+/- 2	+/- 1.6	%	ISO 5077



COLOUR-FASTNESS

Colour fastness UV - outdoor - 1000h	4-5		Class / 5	ISO 105 B04
Colour fastness UV - indoor	7-8		Class / 8	ISO 105 B02
Colour fastness under dry friction	5		Class / 5	ISO 105X12
Colour fastness under wet friction	5		Class / 5	ISO 105X12
Colour fastness 40°C washing	5		Class / 5	ISO 105 C06

USES

Guarantee	5	years	
Recommended Uses	Cushions, Seating, Planking		

CARE



This product's values may vary with a tolerance of $\pm 5\%$

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com/en/UK