

SUNBRELLA RUSH

Technical sheet



CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

GENERAL CHARACTERISTICS

Composition	100% Sunbrella acrylic		
Backing / Finish	Water-repellent & Stain-proof		
Weave	Jacquard		ISO 7211-1
Weight	331		g/m ² ISO 3801
Width	140		cm EN 1773
Roll length	50		ml



FABRIC RESISTANCE

Tensile strength	176	89	daN/5cm	ISO 13934-1
Elongation at break	24	27	%	ISO 13934-1
Schmerber	160		mm	ISO 811
Spray test	5		Class / 5	ISO 4920
Oil-resistance properties	5		Class / 8	ISO 14419
Seam slippage (180 N)	< 3	< 4	mm	ISO 13936-2
Stitching strength	586	563	daN	ISO 13935-2
Stability on 30 deg. C washing	+/- 1.8	+/- 0.8	%	ISO 5077



COLOUR-FASTNESS

Colour fastness UV - outdoor - 1000h	4-5		Class / 5	ISO 105 B04
Colour fastness UV - indoor	7-8		Class / 8	ISO 105 B02
Colour fastness under dry friction	5		Class / 5	ISO 105X12
Colour fastness under wet friction	5		Class / 5	ISO 105X12
Colour fastness 40°C washing	5		Class / 5	ISO 105 C06

USES

Guarantee	5	years	
Recommended Uses	Cushions, Curtains, Roman blinds, Seating		

CARE



This product's values may vary with a tolerance of ± 5%

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com/en/UK