

ORCHESTRA MAX

Technical sheet

CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

GENERAL CHARACTERISTICS

Composition	100% solution dyed acrylic Sunacryl		
Backing / Finish	Water repellent treatment - easy to clean. Coating one side waterproof and UV - resistant		
Weave	Canvas		ISO 7211-1
Weight	320	g/m ²	ISO 3801
Thickness	0.7	mm	ISO 5084
Width	120	cm	EN 1773
Roll length	60	ml	

FABRIC RESISTANCE

Tensile strength	154	105	daN/5cm	ISO 13934-1
Elongation at break	37	32	%	ISO 13934-1
Tear strength	3	2	daN	ISO 13937-1
Stiffness	950	680	mN	ISO 2493
Elongation under load	3	7	%	MO LAB 025
Schmerber	1200		mm	ISO 811
Spray test	4-5		Class / 5	ISO 4920
Oil-resistance properties	6		Class / 8	ISO 14419
Resistance durability	4		Class / 4	EN 13561

COLOUR-FASTNESS

Colour fastness UV - outdoor - 1000h	4-5	Class / 5	ISO 105 B04
Colour fastness UV - indoor	7-8	Class / 8	ISO 105 B02
Colour fastness under dry friction	5	Class / 5	ISO 105X12
Colour fastness under wet friction	5	Class / 5	ISO 105X12
Colour durability	4	Class / 4	EN 13561

USES

Guarantee	10	years	
Recommended Uses	Drop arm awning, Folding arm awning, Dutch canopy, Fixed awning, Exterior velum, Sail shade, Conservatory blind, Pergola		

This product's values may vary with a tolerance of ± 5%

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com/en/UK



WARRANTY

MASS
DYED

COLOURS

MADE IN



FRANCE