

# BLEND

## Technical sheet



CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

### GENERAL CHARACTERISTICS

Composition	97% Sunbrella Acrylic - 3% PE		
Backing / Finish	Water-repellent & Stain-proof		
Weave	Natté		ISO 7211-1
Weight	320.00	GMET	ISO 3801
Width	137	CM	EN 1773
Roll length	50	ML	

### FABRIC RESISTANCE

Pilling	3/4		CLA5	ISO 12945-2
Spray test	2		CLA5	ISO 4920
Seam slippage (180 N)	<1	<3	MM	ISO 13936-2
Stability on 30 deg. C washing	±2	±1	%	ISO 5077

### COLOUR-FASTNESS

Colour fastness UV - outdoor - 1000h	5		CLA5	ISO 105 B04
Colour fastness UV - indoor	8		CLA8	ISO 105 B02
Colour fastness under dry friction	5		CLA5	ISO 105X12
Colour fastness under wet friction	5		CLA5	ISO 105X12
Colour fastness 40°C washing	5		CLA5	ISO 105 C06

### USES

Guarantee	5	YE	
Recommended Uses	seating, cushions		

### CARE



*This product's values may vary with a tolerance of ± 5%*

**Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration**

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - [www.dickson-constant.com/en/UK](http://www.dickson-constant.com/en/UK)

