

# ORCHESTRA MAX

## Technical sheet

CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		



### GENERAL CHARACTERISTICS

Composition	100% solution dyed acrylic Sunacryl			
Backing / Finish	Water repellent treatment - easy to clean. Coating one side waterproof and UV - resistant			
Weave	Canvas			ISO 7211-1
Weight	320.00		GMET	ISO 3801
Thickness	0.70		MM	ISO 5084
Width	120		CM	EN 1773
Roll length	60		ML	

### FABRIC RESISTANCE

Tensile strength	154.00	105.00	DAN5	ISO 13934-1
Elongation at break	37	32	%	ISO 13934-1
Tear strength	3.00	2.00	DAN	ISO 13937-1
Stiffness	950	680	MN	ISO 2493
Elongation under load	3	7	%	MO LAB 025
Schmerber	1200		MM	ISO 811
Spray test	4-5		CLA5	ISO 4920
Resistance durability	4		CLA4	EN 13561

### COLOUR-FASTNESS

Colour fastness UV - outdoor - 1000h	4-5		CLA5	ISO 105 B04
Colour fastness UV - indoor	7-8		CLA8	ISO 105 B02
Colour fastness under dry friction	5		CLA5	ISO 105X12
Colour fastness under wet friction	5		CLA5	ISO 105X12
Colour durability	4		CLA4	EN 13561

### USES

Guarantee	10		YE	
Recommended Uses	Drop arm awning, Folding arm awning, Dutch canopy, Fixed awning, Exterior velum, Sail shade, Conservatory blind, Pergola			

*This product's values may vary with a tolerance of ± 5%*

**Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration**

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - [www.dickson-constant.com/en/UK](http://www.dickson-constant.com/en/UK)



WARRANTY

MASS  
DYED

COLOURS

MADE IN



FRANCE