

SUNBRELLA DROPS

Technical sheet



CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

GENERAL CHARACTERISTICS

Composition	100% Sunbrella acrylic			
Backing / Finish	Water-repellent & Stain-proof			
Weave	Jacquard			ISO 7211-1
Weight	342.00		GMET	ISO 3801
Width	140		CM	EN 1773
Roll length	50		ML	

FABRIC RESISTANCE

Tensile strength	186.00	98.00	DAN5	ISO 13934-1
Elongation at break	25	28	%	ISO 13934-1
Schmerber	150		MM	ISO 811
Spray test	5		CLA5	ISO 4920
Seam slippage (180 N)	< 2	< 5	MM	ISO 13936-2
Stitching strength	543	617	DAN	ISO 13935-2
Stability on 30 deg. C washing	+/- 1.6	+/- 1.4	%	ISO 5077

COLOUR-FASTNESS

Colour fastness UV - outdoor - 1000h	4-5		CLA5	ISO 105 B04
Colour fastness UV - indoor	7-8		CLA8	ISO 105 B02
Colour fastness under dry friction	5		CLA5	ISO 105X12
Colour fastness under wet friction	5		CLA5	ISO 105X12
Colour fastness 40°C washing	5		CLA5	ISO 105 C06

USES

Guarantee	5		YE	
Recommended Uses	Cushions,Curtains,Roman blinds,Seating			

CARE



This product's values may vary with a tolerance of $\pm 5\%$

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com/en/UK

