

SUNT2

Technical sheet



CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

GENERAL CHARACTERISTICS

Composition	100% Sunbrella® Acrylic			
Backing / Finish	Water repellent treatment - easy to clean. Polyurethane coating one side water and UV - resistant			
Weave	Canvas			ISO 7211-1
Weight	320.00		GMET	ISO 3801
Width	152		CM	EN 1773
Roll length	50		ML	

FABRIC RESISTANCE

Tensile strength	140.00	130.00	DAN5	ISO 13934-1
Elongation at break	30	15	%	ISO 13934-1
Tear strength	3.30	2.50	DAN	ISO 13937-1
Schmerber	1000		MM	ISO 811
Spray test	4		CLA5	ISO 4920

COLOUR-FASTNESS

Colour fastness UV - outdoor - 1000h	4-5		CLA5	ISO 105 B04
Colour fastness UV - indoor	7-8		CLA8	ISO 105 B02
Colour fastness under dry friction	5		CLA5	ISO 105X12
Colour fastness under wet friction	5		CLA5	ISO 105X12

USES

Guarantee	5		YE	
Recommended Uses	Sprayhood, Rear enclosure, Bimini top, Cockpit enclosure, Windscreen cover, Dodger, Console cover, Lazybag			

This product's values may vary with a tolerance of ± 5%

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com/en/UK



Tested for harmful substances.
www.oeko-tex.com/standard100

