

# SURLAST

## Technical sheet



CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

### GENERAL CHARACTERISTICS

Composition	100% polyester teint masse			
Backing / Finish	Polyuréthane coating			
Weight	240		g/m <sup>2</sup>	ISO 3801
Width	152		cm	EN 1773
Roll length	90		m	



### FABRIC RESISTANCE

Tensile strength	217	152	daN/5cm	ISO 13934-1
Tear strength	9.9	8.7	daN	ISO 13937-1
Schmerber	850		mm	ISO 811

### COLOUR-FASTNESS

Colour fastness UV - outdoor - 1000h	4		Class / 5	ISO 105 B04
--------------------------------------	---	--	-----------	-------------

### USES

Guarantee	3		years	
Recommended Uses	Bimini top, Console cover, Seat cover			

*This product's values may vary with a tolerance of ± 5%*

**Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration**

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - [www.dickson-constant.com/en/UK](http://www.dickson-constant.com/en/UK)