

SUNBRELLA FURLING ADHESIVE





Technical sheet

CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

GENERAL CHARACTERISTICS

Composition	100% Sunbrella acrylic		
Backing / Finish	Special marine treatment		
Weave	Canvas		ISO 7211-1
Weight	250	g/m ²	ISO 3801
Width	150	cm	EN 1773
Roll length	50	m	

WARRANTY	MADE IN
MASS DYED 	
COLOURS	FRANCE

FABRIC RESISTANCE

Tensile strength	135	40	daN/5cm	ISO 13934-1
Tear strength	2.8	1.6	daN	ISO 13937-1
Schmerber	240		mm	ISO 811
Spray test	5		Class / 5	ISO 4920

COLOUR-FASTNESS

Colour fastness UV - outdoor - 1000h	4-5	Class / 5	ISO 105 B04
Colour fastness UV - indoor	7-8	Class / 8	ISO 105 B02

USES

Recommended Uses	UV Protection strip on Furling Sails
------------------	--------------------------------------

This product's values may vary with a tolerance of ± 5%

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com/en/UK