

SUNVISION

Technical sheet



CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

GENERAL CHARACTERISTICS

Composition	Fil Polyester haute ténacité enduit PVC (58%), fil acrylique teint masse (42%)		
Backing / Finish	Traitement Cleangard spécial store antisalissures et imperméabilisant		
Weave	Toile		ISO 7211-1
Weight	275		g/m ² ISO 3801
Thickness	0.74		mm ISO 5084
Openess factor	12		%
Width	125 250		cm EN 1773
Roll length	50 50		ml



FABRIC RESISTANCE

Tensile strength	80	80	daN/5cm	ISO 13934-1
Elongation at break	23	23	%	ISO 13934-1
Tear strength	5	5	daN	ISO 13937-1
Elongation under load	8	10	%	MO LAB 025
Resistance durability	4		Class / 4	EN 13561

COLOUR-FASTNESS

Colour fastness UV - outdoor - 1000h	4-5		Class / 5	ISO 105 B04
Colour fastness UV - indoor	7-8		Class / 8	ISO 105 B02
Colour durability	4		Class / 4	EN 13561

USES

Temperature of use	-30 >> +70		
Guarantee	5	years	
Recommended Uses	Store à projection, Vélum extérieur, Pergola, Voile d'ombrage, Store intérieur, Panneau de séparation, Lambrequin enroulable, Screen pergola		

This product's values may vary with a tolerance of ± 5%

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com/en/UK

